SAFETY DATA SHEET

1. Identification

Product identifier	FS Industrial Hydraulic Oil 32		
Other means of identification	None.		
Recommended use	Hydraulic Oil		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/	Distributor information		
Manufacturer			
Company name	GROWMARK INC.		
Address	2200 South Avenue		
	Council Bluffs, IA 51503 United States		
Telephone	General Assistance	800-798-6457	
E-mail	Not available.		
Emergency phone number	CHEMTREC	800-424-9300	
2. Hazard(s) identification			
Physical hazards	Not classified.		
Health hazards	Carcinogenicity		Category 1A
Environmental hazards	Not classified.		
OSHA defined hazards	Not classified.		
Label elements			
Signal word	Danger		
Hazard statement	May cause cancer.		
Precautionary statement			
Prevention			handle until all safety precautions have been read ctive clothing/eye protection/face protection.
Response	If exposed or concerned: Get medical advice/attention.		
Storage	Store locked up.		
Disposal	Dispose of contents/container i	in accordance w	vith local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.		
Supplemental information	None.		

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Lubricating Oils (petroleum), Hydrotreated Spent		64742-58-1	67.08
Distillates (petroleum), solvent-dewaxed heavy paraffinic		64742-65-0	31.57
ALKYL PHENOL		Proprietary	< 0.2
SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.		64742-94-5	<0.1
Other components below reportable leve	els		1-<3

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	

0 0	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
,		2000 mg/m3	

Components	for Air Contaminants (29 CFR 1910.10 Type	Value	Form		
		500 ppm			
SOLVENT NAPHTHA	PEL	400 mg/m3			
(PETROLEUM), HEAVY AROM. (CAS 64742-94-5)					
AROM. (CAS 64742-94-5)		100 ppm			
US. ACGIH Threshold Limit	Values				
Components	Туре	Value	Form		
Distillates (petroleum), solvent-dewaxed heavy	TWA	5 mg/m3	Inhalable fraction.		
paraffinic (CAS 64742-65-0)					
Lubricating Oils	TWA	5 mg/m3	Inhalable fraction.		
(petroleum), Hydrotreated Spent (CAS 64742-58-1)					
SOLVENT NAPHTHA	TWA	200 mg/m3	Non-aerosol.		
(PETROLEUM), HEAVY AROM. (CAS 64742-94-5)		Loonighio			
US. NIOSH: Pocket Guide to	Chemical Hazards				
Components	Туре	Value	Form		
Distillates (petroleum), solvent-dewaxed heavy	Ceiling	1800 mg/m3			
paraffinic (CAS 64742-65-0)	STEL	10 mg/m3	Mist.		
logical limit values	No biological exposure limits noted for the ingredient(s).				
oosure guidelines					
US ACGIH Threshold Limit	Values: Skin designation				
SOLVENT NAPHTHA (F (CAS 64742-94-5)	ETROLEUM), HEAVY AROM. Can b	be absorbed through the skin.			
propriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.				
ividual protection measures	, such as personal protective equipm				
Eye/face protection	If contact is likely, safety glasses with		d.		
Skin protection					
Hand protection	For prolonged or repeated skin contact	For prolonged or repeated skin contact use suitable protective gloves.			
Other	Wear suitable protective clothing.				
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.				
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.				
neral hygiene hsiderations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.				
Physical and chemical p	properties				
bearance	-				
Physical state	Liquid.				

Physical state	Liquid.
Form	Liquid.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.

Initial boiling point and boiling range	680 °F (360 °C) estimated
Flash point	275.0 °F (135.0 °C) estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	500 °F (260 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Density	7.33 lbs/gal estimated
Flammability class	Combustible IIIB estimated
Percent volatile	0.00002 % estimated
Specific gravity	0.88 estimated
VOC (Weight %)	0.00002 % estimated
10. Stability and reactivity	

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.	
Skin contact	No adverse effects due to skin contact are expected.	
Eye contact	Direct contact with eyes may cause temporary irritation.	
Ingestion	Expected to be a low ingestion hazard.	
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.	
Information on toxicological effects		

Acute toxicity

Components	Species		Test Results	
SOLVENT NAPHTHA (PETROI	EUM), HEAVY	AROM. (CAS 64742-94-5)		
Acute				
Inhalation				
LC50	Rat		61 mg/l, 4 Hours	
Oral				
LD50	Rat		> 25 ml/kg	
* Estimates for product may	/ be based on ac	dditional component data not shown.		
Skin corrosion/irritation	•	skin contact may cause temporary irrita		
Serious eye damage/eye irritation	Direct cont	act with eyes may cause temporary irritat	ion.	
Respiratory or skin sensitizat				
Respiratory sensitization	Not a respi	iratory sensitizer.		
Skin sensitization	This produc	ct is not expected to cause skin sensitizati	on.	
Germ cell mutagenicity		vailable to indicate product or any compo or genotoxic.	nents present at greater than 0.1% are	
Carcinogenicity	May cause	cancer.		
OSHA Specifically Regulat Not listed. US. National Toxicology I		(29 CFR 1910.1001-1050) Report on Carcinogens	9	
Distillates (petroleum) (CAS 64742-65-0) Lubricating Oils (petro 64742-58-1)		ed heavy paraffinic Known To Be Huma ated Spent (CAS Known To Be Huma		
Reproductive toxicity	This produ	ct is not expected to cause reproductive	or developmental effects.	
Specific target organ toxicity single exposure	- Not classifi	ied.	-	
Specific target organ toxicity repeated exposure	- Not classifie	ed.		
Aspiration hazard	Not an asp	viration hazard.		
Chronic effects	Prolonged	inhalation may be harmful.		
12. Ecological informatio	n			
Ecotoxicity			azardous. However, this does not exclude the rmful or damaging effect on the environment.	
Components		Species	Test Results	
	ROLEUM), HEA	AVY AROM. (CAS 64742-94-5)		
Aquatic				
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours	
			8.8 mg/l, 96 hours	
* Estimates for product ma	v be based on a	additional component data not shown.		
Persistence and degradability	-	available on the degradability of this prod	duct.	
Bioaccumulative potential				
Mobility in soil	No data ava	ailable.		
Other adverse effects		No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		
13. Disposal consideration	ons			
Disposal instructions		d reclaim or dispose in sealed containers	at licensed waste disposal site. Dispose of	
Local disposal regulations	contents/co	ontainer in accordance with local/regiona accordance with all applicable regulations	l/national/international regulations.	
Material name: FS Industrial Hy	draulic Oil 32		SDSU	
material name. Le maastial Hy			3030	

Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. One or more components are not listed on TSCA.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

US federal regulations

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting) Not regulated.

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0) Lubricating Oils (petroleum), Hydrotreated Spent (CAS 64742-58-1)

SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS 64742-94-5)

US. Massachusetts RTK - Substance List

Distillates (petroleum), solvent-dewaxed heavy paraffinic (CAS 64742-65-0)

US. New Jersey Worker and Community Right-to-Know Act SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM. (CAS 64742-94-5)

US. Pennsylvania Worker and Community Right-to-Know Law

Not listed.

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory		

*A 'Yes' indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A 'No' indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	04-22-2015
Version #	01
Disclaimer	GROWMARK Lubricants cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

X